

ELLBRAID REINFORCED WATER HOSE

CH Series



A high quality hose that is supplied for industrial-scale farmers worldwide, and one that is renowned for its flexibility, performance and reliability. The design incorporates Copely's Spiralap technology for a longer lifespan.

Key Features:

- Good flexibility.
- Effective kink resistance.
- Good abrasion resistance.
- Made from Cadmium-free materials.
- Silicone-free.
- Suitable for use at -15°C to +60°C.
- Specially selected high tensile Polyester fiber reinforcement used at the optimum braid angle of 54° 44'(54.73°) creates an effectively balanced pressure hose.
- Inner layer is made from a carefully controlled recycled material.
- Conforms to BS 3746.
- Safety Factor: 3:1.
- RoHS 3 compliant.

Sizes:

CH12: Available in 15m, 30m, 75m and 100m coils

CH19: Available in 25m and 50m coils

CH25: Available in 25m and 50m coils

Colours:

Red with black inner



1. DEHP free PVC inner
2. Polyester fiber reinforcement
3. DEHP free PVC outer



Applications:

- Fresh produce industry - industrial growers
- Building sites



Product Ref	Internal Diameter	External Diameter	Maximum Working Pressure	Minimum Burst Pressure
CH12	12.5mm	17.25mm	10 Bar Max @ 20°C	30 Bar Min @ 20°C
CH19	19.25mm	24.12mm	10 Bar Max @ 20°C	30 Bar Min @ 20°C
CH25	25mm	31.25mm	10 Bar Max @ 20°C	30 Bar Min @ 20°C