

# COMPACT PREFORMED AIRLINE COILS

## EC Series



An off-the-shelf solution satisfying all market sectors requiring a lightweight Type 12 Nylon airline coil with high resistance to oil, organic and non-organic media.

### Key Features:

- Excellent flexibility / retention.
- Light weight.
- Superior flow characteristics.
- BSPT Male Swivel fittings (compression) complete with anti-kink spring.
- Suitable for horizontal and vertical applications.
- Temperature range -40oC to +80oC.
- Maximum Working Pressure = 15 bar.
- RoHS 3 compliant.

### Sizes:

8mm, 10mm & 12mm OD in working lengths of 2.5m, 5m, 10m and 15m  
Fittings 1/4 BSPT and 3/8 BSPT

### Colours:

Red  
Blue

Other colours available on request



1. BSP Male Swivel With Spring Guards
2. Impact modified PA12



### Applications:

- Industrial air tools
- Production line assembly

Product Ref	Tube Size	Working Length (m)				Number of turns				Tail Lengths	Coil Diameter	Fittings
		2.5m	5m	10m	15m	13	27	55	86			
EC08	8 x 6mm	2.5m	5m	10m	15m	13	27	55	86	500 / 100mm	76mm	1/4" BSP Male Swivel With Spring Guards
EC10	10 x 8mm	2.5m	5m	10m	-	13	26	53	-	500 / 100mm	76mm	1/4" BSP Male Swivel With Spring Guards
EC12	12 x 9mm	2.5m	5m	10m	-	11	23	46	-	500 / 100mm	90mm	3/8" BSP Male Swivel With Spring Guards