LOW DENSITY POLYETHYLENE











A low cost hosing solution for an extensive range of applications for use in ambient conditions. Low Density Polyethylene flexible tubing is a popular choice for the brewery industry for the conveyance of beer and soft drinks, as well as water for domestic services.

Key Features:

- High impact strength at low temperatures.
- Resistant to many liquids and chemicals.
- Low toxic.
- FDA approved.
- Silicone-free.
- Very flexible.
- 3:1 safety factor.

Sizes:

Available in 30m coils 4mm, 6mm, 8mm, 10mm & 12mm OD

Colours:

Natural

White

Blue

Black

White, Blue and Black are subject to a minimum order quantity.



1. Polyethylene



Applications:

- Conveyance of beer and soft drinks.
- Domestic drinking water systems.
- Water treatment industry for chemical dosing.
- Scientific and pharmaceutical chemical transfer.











Product Ref	Internal Diameter	External Diameter	Maximum Working Pressure	Minimum Burst Pressure	Weight per coil
LDP04	2.5mm	4mm	20 Bar	60 Bar	0.22 Kg
LDP06	4mm	6mm	17 Bar	51 Bar	0.44 Kg
LDP08	6mm	8mm	12 Bar	36 Bar	0.61 Kg
LDP10	8mm	10mm	10 Bar	30 Bar	0.79 Kg
LDP12	10mm	12mm	12 Bar	24 Bar	0.97 Kg