

NYLON TUBING

FLEXIBLE - IMPERIAL SIZES

NMF Series



All the features of the Flexible Nylon tubing but provided in imperial tube dimensions. Industrial tubing made from flexible nylon. Ideally suited for pneumatic/hydraulic applications such as air brakes, as well as fuel and lube applications. Also ideal for low toxic or high temperature environments such as breweries or applications involving food contact.

Key Features:

- Flexible, lightweight and durable over a wide temperature range.
- Smooth inner for improved flow.
- Manufactured from heat and light stabilised Nylon to precise tolerances.
- Available on dispensing drums to special order.
- Resistant to a wide range of chemicals.
- High resistance to moisture absorption.
- Silicone-free.
- Excellent abrasion resistance.
- 4:1 safety factor.
- RoHS 3 compliant.

Sizes:

Available in 30m coils.
Longer lengths available to order
1/8" to 1" OD

Colours:

Natural, black, other colours available on request




1. Impact modified PA12



Applications:

- Air brake, fuel and lube applications as well as secondary air systems



Product Ref	Internal Diameter		External Diameter		Maximum Working Pressure	Minimum Burst Pressure	Weight per Metre	Bend Radius	
NMF04	0.075"	1.90mm	1/8"	3.18mm	26 Bar	104 Bar	0.005 Kg	3/4"	19mm
NMF05	0.117"	2.97mm	3/16"	4.76mm	24 Bar	96 Bar	0.011 Kg	3/4"	19mm
NMF06	0.170"	4.32mm	1/4"	6.35mm	22 Bar	88 Bar	0.017 Kg	1"	25mm
NMF08	0.212"	5.40mm	5/16"	7.94mm	22 Bar	88 Bar	0.028 Kg	1 1/2"	38mm
NMF10	0.250"	6.35mm	3/8"	9.53mm	21 Bar	84 Bar	0.041 Kg	2"	51mm
NMF12	0.375"	9.52mm	1/2"	12.70mm	18 Bar	72 Bar	0.057 Kg	2"	51mm
NMF16	0.500"	12.70mm	5/8"	15.88mm	16 Bar	64 Bar	0.073 Kg	3 1/2"	89mm
NMF20	0.594"	15.00mm	3/4"	19.05mm	16 Bar	64 Bar	0.109 Kg	6"	152mm
NMF25	0.812"	20.63mm	1"	25.40mm	15 Bar	60 Bar	0.177 Kg	9"	228mm