

AQUAVEND UNREINFORCED PH SERIES



A high quality, low pressure tube finished in ultra-clean brilliant white designed primarily for the conveyance of mains cold water, incorporating innovative co-extrusion technology for flexibility and durability.

Key Features:

- Aquavend will not support microbiological growth in accordance with BS 6920.
- WRAS approved construction.
- Cadmium and silicone-free.
- High quality PVC outer extruded with a brilliant white 'clinical' finish.
- TPE mirror smooth inner for improved flow.
- Odourless and specialist material prevents tainting the taste of water.
- Good flexibility and durability.
- Excellent resistance to abrasion.
- Compatible with latest push-in fittings.
- NB: Routing of this tubing should not run in close proximity to hot water pipes and other heat sources.
- Independently tested in accordance with BS 6920.
- 3:1 safety factor @ -20°C.
- RoHS 3 compliant.

Sizes:

Available in 30m coils
6.4mm & 9.5mm OD

Custom sizes available on request subject to minimum order quantity

Colours:

Black Inner / White outer




1. Thermoplastic Polyester Elastomer
2. Phthalate free PVC



Applications:

- Drinking water
- Petrochemical
- Low pressure brine tubing
- Water transfer
- Chemical
- Hydrocarbon transfer



Product Ref	Internal Diameter	External Diameter	Maximum Working Pressure	Minimum Burst Pressure	Weight per Metre	Bend Radius
PH06	4.325mm	6.375mm	10 Bar	30 Bar	0.028 Kg	57mm
PH08	6.3mm	9.525mm	10 Bar	60 Bar	0.543 Kg	86mm