

RUBBER AIR HOSE

RAH Series



A black, weather and ozone resistant compressed air hose suitable for general workshop use and compressors.

Manufactured from NBR / SBR synthetic rubber with high tensile synthetic textile reinforcement. Medium duty service for air and pneumatic tools including workshops with compressors, mines, quarries and construction.

Key Features:

- Abrasion, ozone and weather resistant.
- Smooth rubber NBR / SBR construction.
- In accordance with EN ISO 2398.
- Wide temperature range 40°C to +90°C.
- Safety factor 3:1.

Sizes:

Available in 25m coils

Colours:

Black




1. NBR/SBR Rubber inner
2. Polyester fibre reinforcement
3. NBR/SBR Rubber outer



Applications:

- Construction
- General workshop use
- Compressors
- Mines
- Quarries



| Product Ref | Internal Diameter | External Diameter | Maximum Working Pressure | Minimum Burst Pressure | Weight per Metre | Bend Radius (Approx.) |
|-------------|-------------------|-------------------|--------------------------|------------------------|------------------|-----------------------|
| RAH06 | 6mm | 12mm | 20 Bar | 60 Bar | 0.18 Kg | 60mm |
| RAH08 | 8mm | 15mm | 20 Bar | 60 Bar | 0.23 Kg | 80mm |
| RAH10 | 10mm | 17mm | 20 Bar | 60 Bar | 0.29 Kg | 100mm |
| RAH13 | 13mm | 21mm | 20 Bar | 60 Bar | 0.43 Kg | 130mm |
| RAH16 | 16mm | 25mm | 20 Bar | 60 Bar | 0.6 Kg | 160mm |
| RAH19 | 19mm | 29mm | 20 Bar | 60 Bar | 0.7 Kg | 190mm |
| RAH25 | 25mm | 36mm | 20 Bar | 60 Bar | 1 Kg | 250mm |