

DELIVERY HOSE

DH Series

Copely



A lightweight delivery hose reinforced with a rigid internal crush and kink resistant white PVC helix. It is tough, flexible and extremely durable. It has outstanding resistance to the effects of weather.

Key Features:

- Lightweight construction for easy handling.
- Optimum flow is maintained by the smooth bore.
- Tough, flexible and extremely durable.
- Retains flexibility, even in cold weather applications.
- Outstanding resistance to the effects of weather.
- Excellent chemical and abrasion resistance.
- RoHS 3 compliant.

Sizes:

- Available from stock in 5 m, 10 m & 30 m coils

Colours:

- Standard – Transparent Green, White Helix



1. Shock resistant rigid PVC reinforcement
2. Flexible Phthalate free PVC



Liquid Transfer

Custom sizes and colours available on request subject to minimum order quantities

Applications:

- Light pressure transfer of liquids, slurries and powders
- Agricultural
- Horticultural
- Marine
- Construction

Product Ref	Internal Diameter	External Diameter	Wall Thickness	Maximum Working Pressure	Weight per Metre	Bend Radius	Vacuum Metres H ₂ O
DH07	19 mm	24.6 mm	2.6 mm	9.0 Bar	0.26 Kg	86 mm	7
DH10	25.4 mm	32 mm	3.3 mm	8.0 Bar	0.33 Kg	114 mm	7
DH12	32 mm	39.2 mm	3.6 mm	7.0 Bar	0.46 Kg	143 mm	7
DH15	38 mm	45.4 mm	3.7 mm	6.5 Bar	0.55 Kg	171 mm	7
DHM45	45 mm	52.8 mm	3.9 mm	6.5 Bar	0.67 Kg	200 mm	7
DH20	51.6 mm	59.8 mm	4.1 mm	6.0 Bar	0.81 Kg	230 mm	7
DH25	63.5 mm	71.9 mm	4.2 mm	5.0 Bar	1.04 kg	284 mm	7
DH30	76 mm	86.4 mm	5.2 mm	4.0 Bar	1.38 Kg	342 mm	7
DH40	102 mm	114.6 mm	6.3 mm	4.0 Bar	2.16 Kg	459 mm	7