

PAINT & FLUID HOSE

EPS Series



A higher pressure, multi-purpose 'four layer' chemical transfer hose suitable for paint, fluid, air and solvents. Light and flexible to use, it is also non-conductive.

Key Features:


- Polyamide liner with a Polyurethane intermediate layer combined with polyester reinforcement and a Polyurethane outer cover for optimum flexibility.
- Fully flexible even at low temperatures – 40°C – +75°C.
- Compatible with most manufacturers' systems when used for spray paint purposes.
- Extremely abrasion resistant.
- Burst pressure 60-80 bar.
- Safety Factor 4:1 as advised by ISO7751:2016.
- RoHS 3 compliant.

Sizes:

- 6.3 mm & 9.52 mm ID available from stock in 30 m coils
- Can be supplied on drums

Colours:

- Emerald Green

 Custom sizes and colours available on request subject to minimum order quantities

Copely



1. Polyamide liner
2. PU intermediate layer
3. Polyester fibre reinforcement
4. PU outer layer



Applications:

- Spray paint
- Fluids



Product Ref	Internal Diameter	External Diameter	Maximum Working Pressure	Minimum Burst Pressure	Weight per Metre	Bend Radius
ESP06	6.3 mm	11.5 mm	20 Bar	80 Bar	0.103 kg	30 mm
ESP10	9.52 mm	15.5 mm	15 Bar	60 Bar	0.166 Kg	40 mm

