

COMPRESSOR HOSE ASSEMBLY

GPA Series



This professional compressor hose assembly, with heavy duty safety claw clamps, is the cost-effective, high-performance TPE alternative to rubber hosing. While looking and feeling like rubber, it has many advantages including a longer lifespan. Manufactured from a hard-wearing PVC Nitrile blend, this ergonomic super-flexible product is a real winner in many industrial environments.

Key Features:


- Professional 15 m air compressor assembly including safety claw clamps.
- PVC Nitrile blend gives good abrasion and ageing resistance – superior to rubber.
- Clean, flexible and user-friendly.
- Reduced Plasticiser migration.
- Excellent resistance to UV / Ozone.
- Silicone and Cadmium free.
- Service Temperature – 15°C – + 60°C.
- 3:1 safety factor.
- **Every hose is fully tested to 20 Bar during manufacture.**

Sizes:

- Available in 15 m coils

Colours:

- Yellow

 Custom sizes and colours available on request subject to minimum order quantities



Copely



1. Double lock quick release coupling (DLQR)
2. Safety clamp with nyloc nuts fitted for additional safety
3. High strength PVC reinforced hose



Applications:

- Compressed air tools
- Spray guns
- Road breakers
- General industrial – oil, grease solvents, air and water applications



Product Ref	Internal Diameter	External Diameter	Wall Thickness	Maximum Working Pressure	Minimum Burst Pressure	Bend Radius (Approx.)
GPA19	19 mm	29 mm	10 mm	20 Bar	60 Bar	170 mm