

FLUTED WATER HOSE

GPW Series

Copely



A robustly constructed reinforced PVC 'fluted' hose which has proven to be the preferred choice for building site contractors and for use in agriculture for the conveyance of water.

Key Features:

- Durable 'fluted' protective outer cover designed to minimise friction.
- Flexible for ease of handling.
- Excellent abrasion resistance.
- Outstanding UV / Ozone resistance.
- Cadmium and Silicone free.
- Conforms to BS 3746: 1990.
- 3:1 safety factor.
- RoHS 3 compliant.

Sizes:

- 13 mm, 19 mm & 25 mm ID available from stock in 40 m coils

Colours:

- Black




1. Phthalate free PVC
2. Polyester fiber reinforcement
3. Phthalate free PVC



Applications:

- Building sites
- Agricultural

 Custom sizes and colours available on request subject to minimum order quantities

Product Ref	Internal Diameter	External Diameter	Maximum Working Pressure	Minimum Burst Pressure	Weight per Metre	Bend Radius
GPW13	13 mm	17.5 mm	7 Bar	21 Bar	0.167 Kg	65 mm
GPW19	19 mm	26 mm	7 Bar	21 Bar	0.350 Kg	135 mm
GPW25	25 mm	32 mm	7 Bar	21 Bar	0.470 Kg	210 mm